

00.00.00 Central extract unit **DucoBox Silent UK 3-pin plug**

serial no. 1

Description:

DucoBox Silent UK 3-pin plug, centrally/non-locally controlled mechanical central extract unit.

Operation:

Wireless communication via RF protocol with other control components within the **DUCO** network.

Material:

Plastic:	Polypropylene
Electric motor:	Supply voltage (VAC): 230 Absorbed power (W): max. 84.39 Type: direct current Thermally protected

Design:

Colour:	Green with white cover
Connectors:	Diameter (mm): 125 No. on extraction side: 1 No. on supply side: 7

Technical specifications

Flow (m ³ /h):	Max. 400
Head (Pa):	150
Dimensions (L x W x H) (mm):	480 x 480 x 195
Weight:	4.3 kg
Sound power level (dB(A)) (at 350 m ³ /h with a head of 100 Pa):	Supply: 57.5 Emission from casing: 46.5

Accessories:

With G Plug power cord (3 x 0.75 mm²/2 m) (standard).

Silent Plus Kit (optional with **Duco Silent System**):

- 3 acoustic blocks in central extract unit.
- 3 acoustic caps on central extract unit.

Application:

Mechanical ventilation installation:
Employed as standard in the **Duco Silent System**.

Fitting:

- Fitting method: In an enclosed installation location against a wall with a mass > 200 kg/m²
- Connectors: Extraction side: fit non-flexible, fixed ducts leading to the outside, the route of which should be as straight and direct as possible; increase in diameter: 125 mm to 160 mm. Use at least 2 extraction openings on the central extract unit, one for ventilating the kitchen and one for ventilating other rooms.
- Connection method: Contact your regional dealer or the project department of **DUCO Ventilation & Sun Control** for commercial and technical assistance (assembly and installation instructions).