

TYPE	DucoSun 150CF Underslung - Mullion 42-62						
DESCRIPTION	External permanent solar shading system						
MULLION TYPE	Mullion 42/62						
SHAPE OF BLADE	Blade 150CF						
PITCH	140 mm						
BLADE WIDTH	150 mm						
BLADE HEIGTH	30 mm						
BLADE ANGLE	60°						
MAX. BLADE LENGTH	6000 mm						
SHIFT DISTANCE	Bracket 350/125/125Max: 50 mm Bracket 500/150/125Max: 150 mm Bracket 650/150/125Max: 300 mm						
MATERIAL	Aluminium : EN AW-6063 T66 (EN 573-3) Mullion : min. 2,5mm Blades : min. 1,3mm Thermoplastic parts : Clips Polyamide PA 6,6 -reinforced with glass fibre Steel parts : Brackets Galvanized (50-60µm) Standard untreated, decorative plate optionally available						
SURFACE TREATMENT	- Standard aluminium anodised (15-20µm) according Qualanod - Polyester powder coated (60-80µm) according Qualicoat Seaside type A - Specific RAL codes and/or textured paint on request						
OPTIONS	- Decorative plate 125/125 & 150/125 - Strut not possible with mullion 42/62						
MAX SPAN WITHOUT FACIA		Bracket 350/125/125		Bracket 500/150/125		Bracket 650/150/125	
# Blades	Projection	B=0mm	B=50mm	B=0mm	B=150mm	B=0mm	B=300mm
6	863	2515	2515	2515	2515	2515	2515
7	1003	2515	2490	2515	2165	2515	2210
8	1143	2125	1970	2125	1740	2515	1800
9	1283	1445	1225	1715	1430	2095	1445
10	1423	935	810	1415	935	1730	935

* all the above mentioned spans apply at a wind pressure of 800Pa.

