

TECHNICAL DATA SHEET



Type	DucoGrille Classic G 20V + options																			
DESCRIPTION	Louvre "build-in" wall grille																			
SHAPE OF BLADE	20V																			
PITCH	20 mm																			
FRAME WIDTH	25 mm																			
EQUAL LEG OUTER FRAME	19 mm																			
FRAME DEPTH	36 mm																			
MIN. DIMENSIONS	Width 200mm, Height 200mm. Exception on request.																			
MESH	- standard with insectmesh 2.3 x 2.3 mm																			
OPTIONS	incl. extra drip tray on the back of the frame test result situation installed in wall																			
MATERIAL	Aluminium : EN AW-6063 T66 (EN 573-3) Profile thickness : min. 1,5mm Thermoplastic parts : Clips Polyamide PA 6,6 -reinforced with glass fibre																			
SURFACE TREATMENT	- standard aluminium anodised (15-20µm) according Qualanod - polyester powder coated (60-80µm) according Qualicoat Seaside type A - specific RAL codes and/or textured paint on request																			
VISUAL FREE AREA	95%																			
PHYSICAL FREE AREA	34%																			
AIR FLOW DATA	<table border="1"> <thead> <tr> <th>(EN13030)</th> <th>+ options</th> </tr> </thead> <tbody> <tr> <td>Ce</td> <td>0,149</td> </tr> <tr> <td>K-factor intake</td> <td>45,04</td> </tr> <tr> <td>Cd</td> <td>0,149</td> </tr> <tr> <td>K-factor exhaust</td> <td>45,04</td> </tr> </tbody> </table>		(EN13030)	+ options	Ce	0,149	K-factor intake	45,04	Cd	0,149	K-factor exhaust	45,04								
(EN13030)	+ options																			
Ce	0,149																			
K-factor intake	45,04																			
Cd	0,149																			
K-factor exhaust	45,04																			
WATER RESISTANCE	<table border="1"> <thead> <tr> <th>(EN13030)</th> <th>+ options</th> </tr> </thead> <tbody> <tr> <td>v = 0 m/s</td> <td>A</td> </tr> <tr> <td>v = 0,5 m/s</td> <td>A</td> </tr> <tr> <td>v = 1 m/s</td> <td>B</td> </tr> <tr> <td>v = 1.5 m/s</td> <td>B</td> </tr> <tr> <td>v = 2 m/s</td> <td>C</td> </tr> <tr> <td>v = 2.5 m/s</td> <td>D</td> </tr> <tr> <td>v = 3 m/s</td> <td>D</td> </tr> <tr> <td>v = 3,5 m/s</td> <td>D</td> </tr> </tbody> </table>		(EN13030)	+ options	v = 0 m/s	A	v = 0,5 m/s	A	v = 1 m/s	B	v = 1.5 m/s	B	v = 2 m/s	C	v = 2.5 m/s	D	v = 3 m/s	D	v = 3,5 m/s	D
(EN13030)	+ options																			
v = 0 m/s	A																			
v = 0,5 m/s	A																			
v = 1 m/s	B																			
v = 1.5 m/s	B																			
v = 2 m/s	C																			
v = 2.5 m/s	D																			
v = 3 m/s	D																			
v = 3,5 m/s	D																			

