



TECHNICAL DATA SHEET

TYPE	DUCOFLAT 80 SR				
DESCRIPTION	Window ventilator, suitable for use with aluminium, PVC or timber windows.				
SELF-REGULATING	Yes				
GLASS REDUCTION	80 mm				
EQUIVALENT AREA	14685 mm ² /m @ 1 Pa				
GEOM. FREE AREA	15000 mm ² /m				
AIRFLOW	49,7 m ³ /h/m @ 2 Pa				
GLASS THICKNESS	24, 28, 32 mm				
TRANSOM	24 mm				
SOUND REDUCTION	27 (0;-1) dB Dne,W (C;Ctr) in open position				
OCTAVE BAND VALUES	at 125 Hz	at 250 Hz	at 500 Hz	at 1000 Hz	at 2000 Hz
	27,2 dB	27,3 dB	24,3 dB	25,6 dB	27,3 dB
WIND TIGHTNESS	Class 3 (650 Pa) in closed position				
WATER TIGHTNESS	Class 5A (200 Pa) in closed position				
CONTROL OPTIONS	Handle, Cord or Rod				
U-VALUE	3,00 W/m ² K				
MAXIMUM LENGTH	2500 mm (split flap from 1500 mm)				
MATERIAL	Aluminium : AlMg Si 0.5 Plastic parts : ASA or ABS				
SURFACE TREATMENT	<ul style="list-style-type: none"> - DAR (Duco Anodic Ral) - Polyester powder coated (60-80µm) in Duco300RAL - Specific RAL colour and/or texture on demand - Dual colour available 				



FITTING OVER THE GLASS		
Glass profile (A)	Glass thickness (B)	Vent depth (C)
30 mm	24 mm	35 mm
34 mm	28 mm	39 mm
38 mm	32 mm	43 mm



TRANSOM	
Transom profile	Vent depth
24 mm	35 mm