


# TECHNICAL DATA SHEET

<b>TYPE</b>	<b>DUCOPLUS 60</b>				
<b>DESCRIPTION</b>	Window ventilator, suitable for use with aluminium, PVC or timber windows.				
<b>SELF-REGULATING</b>	No				
<b>GLASS REDUCTION</b>	60 mm				
<b>EQUIVALENT AREA</b>	14224 mm <sup>2</sup> /m @ 1 Pa				
<b>GEOM. FREE AREA</b>	15000 mm <sup>2</sup> /m				
<b>AIRFLOW</b>	56,7 m <sup>3</sup> /h/m @ 2 Pa				
<b>GLASS THICKNESS</b>	20, 24, 28 or 32 mm				
<b>SOUND REDUCTION</b>	25 (0;0) dB D <sub>ne,W</sub> (C;Ctr) in open position				
<b>OCTAVE BAND VALUES</b>	<b>at 125 Hz</b>	<b>at 250 Hz</b>	<b>at 500 Hz</b>	<b>at 1000 Hz</b>	<b>at 2000 Hz</b>
	27,5 dB	31 dB	27,2 dB	24,4 dB	24,2 dB
<b>WIND TIGHTNESS</b>	Class 3 (650 Pa) in closed position				
<b>WATER TIGHTNESS</b>	Class E650 (650 Pa) in closed position				
<b>CONTROL OPTIONS</b>	Handle, Cord or Rod				
<b>U-VALUE</b>	4,02 W/m <sup>2</sup> K				
<b>MAXIMUM LENGTH</b>	2500 mm (split flap from 1500 mm)				
<b>MATERIAL</b>	Aluminium : AlMg Si 0.5 Plastic parts : ASA or ABS				
<b>SURFACE TREATMENT</b>	<ul style="list-style-type: none"> <li>- DAR (Duco Anodic Ral)</li> <li>- Polyester powder coated (60-80µm) in Duco300RAL</li> <li>- Specific RAL colour and/or texture on demand</li> <li>- Dual colour available</li> </ul>				



<b>FITTING OVER THE GLASS</b>	
Glass profile (A)	Glass thickness (B)
26 mm	20 mm
30 mm	24 mm
34 mm	28 mm
38 mm	32 mm