


TECHNICAL DATA SHEET


DucoFlex Roof feed-through Compact D160 - Terracotta



The DucoFlex Roof feed-through Compact D160 can be used as a supply and extraction point. The terracotta colour and the design allow this unit to be integrated very discretely into a tiled roof. The pre-fitted lead slate ensures quick and water-tight installation. Thanks to its smart design, this compact roof feed-through is hardly sensitive to atmospheric turbulence. The connection piece fits seamlessly into the DucoFlex ISO D160 pipes.

Physical characteristics

Article number	0000-4580
Width x Height x Depth (mm)	Total: 390 x 287 x 500 Above the roof: 300 x 147 x 252
Specific features	<ul style="list-style-type: none"> • Very low pressure losses (see graphs) • Transit perpendicular to the roof slope • Pre-assembled lead slate for use in pitched roofs • Application range: Sloping roofs between 5° and 45°
Connection diameter (mm)	D160
Material	Aluminium / galvanised steel / lead
Colour outside	Terracotta
Packaging	Packaged individually



Dimensions (mm)

A	B	C	D	E	F	G	H
60	252	300	160	82	500	390	140

Technical features

Range of application	Outlet / inlet
Maximum flow rate	Outlet: 400 m³/h Inlet: 325 m³/h

