# DucoVent Comfort

Smart vent for project construction





Easy to set up

Adjusted even before mounting



Unique design

Supply and extraction in one vent



**Smart calibration** 

Thanks to 11 adjustment positions



## DucoVent Comfort

#### **GENERAL FEATURES**

#### Maximum flow rate:

Extract air: 75 m<sup>3</sup>/h Supply air: 75 m<sup>3</sup>/h

#### Colour:

White (other RAL colours on request)

#### Mounting:

Suitable for ceiling and wall min. 180 cm above floor level min. 35 cm from the wall

### Ø Duct connection:

125 mm - rubber fixing ring

#### Calibration:

11 adjustment positions

The DucoVent **Comfort** vent is a simple and timeless vent that focuses on both aesthetics and ease of adjustment. It is designed for serial construction projects and can serve as a **supply or extract diffuser**. The design cover plate can be easily disassembled for adjustment and this can be done before or during installation. Moreover, the end user can remove the vent completely without touching the cover plate: this way the vent is not disrupted.

The adjustment position is further secured by a unique shielding principle of the cover plate. This vent is an ideal addition to the DUCO ventilation systems

that use the **copy function** for serial construction. Saving time combined with ease of installation!



Airtight connection thanks to rubber mounting ring

Fine tuning with 11 adjustment positions



9

# LET'S CONNECT! SEND US YOUR PROJECT!

DUCO offers project support from a to z. Get in touch with one of our advisors (digitally). Tel. +32 58 33 00 33



### SCAN the QR code

or visit

www.duco.eu/en/lets-connect

